

3440



Hose construction:	Inner tube:	Reinforcement:	Cover:
	Polyolefin	Synthetic fiber	Polyvinylchloride

Operating temperature: For water-based fluids: -23 °C to +66 °C (-10 °F to +150 °F)

Hose color(s): Blue perforated

Approved Fitting: 4T 

Part #	Size Dimensions						Pressure				Bend		Weight		Length	
	Hose Size	Hose I.D.			Hose O.D.		Max Operating Pressure		Burst Pressure		Min. Bend Radius		Weight		Length	
		DN	mm	in	mm	in	bar	psi	bar	psi	mm	in	Kg/m	lbs./ft	m	ft
3440-04	-04	6	6,4	0.25	13,2	0.52	190	2,750	758	11,000	32,0	1.25	0,09	0.06	76,2	250
3440-06	-06	10	9,5	0.38	16,6	0.66	155	2,250	620	9,000	51,0	2.00	0,13	0.09	76,2	250
3440-08	-08	12	12,7	0.50	20,6	0.81	138	2,000	552	8,000	76,0	3.00	0,18	0.12	76,2	250
3440-12	-12	19	19,0	0.75	29,0	1.14	103	1,500	414	6,000	127,0	5.00	0,36	0.24	76,2	250
3440-16	-16	25	25,4	1.00	37,0	1.46	103	1,500	414	6,000	203,0	8.00	0,55	0.37	76,2	250



Chemical

- Chemical transfer
- Foam system