

34PW

Meets or exceeds: **NSF-61**

Synflex by Danfoss 34PW

Hose construction:	Inner tube:	Reinforcement:	Cover:
	Polyolefin	Synthetic fiber	Polyurethane

Operating temperature: For water-based fluids: -23 °C to +66 °C (-10 °F to +150 °F)

Hose color(s): Blue, non- perforated

Approved Fitting: 4T 

Part #	Size Dimensions						Pressure				Bend		Weight		Length	
	Hose Size	Hose I.D.		Hose O.D.			Max Operating Pressure		Burst Pressure		Min. Bend Radius		Weight		Length	
		DN	mm	in	mm	in	bar	psi	bar	psi	mm	in	Kg/m	lbs./ft	m	ft
34PW-04	-04	6	6,4	0.25	13,2	0.52	190	2,750	758	11,000	32,0	1.25	0,09	0.06	76,2	250
34PW-06	-06	10	9,5	0.38	16,6	0.66	155	2,250	620	9,000	51,0	2.00	0,13	0.09	76,2	250
34PW-08	-08	12	12,7	0.50	20,6	0.81	138	2,000	552	8,000	76,0	3.00	0,24	0.16	76,2	250
34PW-12	-12	19	19,0	0.75	29,0	1.14	103	1,500	414	6,000	127,0	5.00	0,36	0.24	76,2	250
34PW-16	-16	25	25,4	1.00	37,0	1.46	103	1,500	414	6,000	203,0	8.00	0,55	0.37	76,2	250



Food and Beverage



Water