

35NG

Meets or exceeds: **NNSI/IAS NGV 4.2 and CSA 12.52**

Size -4



Size -3; -6 and -8



Hose construction:	Inner tube:	Reinforcement:	Cover:
	Nylon-lines	Synthetic fiber	Polyurethane

Operating temperature: For water-based fluids: -40 °C to +66 °C (-40 °F to +150 °F)

Hose color(s): Black perforated

Approved Fitting: 90H/9MH/90L



Part #	Size Dimensions						Pressure				Bend		Weight		Length	
	Hose Size	Hose I.D.		Hose O.D.			Max Operating Pressure		Burst Pressure		Min. Bend Radius		Weight		Length	
		DN	mm	in	mm	in	bar	psi	bar	psi	mm	in	Kg/m	lbs./ft	m	ft
35NG-03	-03	5	5,2	0.19	13,0	0.51	345	5,000	1,379	20,000	38,0	1.50	0,12	0.08	76,2	250
35NG-04	-04	6	6,4	0.25	16,0	0.63	345	5,000	1,379	20,000	51,0	2.00	0,16	0.11	76,2	250
3GNG-06	-06	10	9,7	0.38	19,5	0.77	345	5,000	1,379	20,000	102,0	4.00	0,22	0.15	76,2	250
35NG-08	-08	12	12,8	0.50	22,5	0.89	345	5,000	1,379	20,000	140,0	5.50	0,31	0.21	76,2	250

- Twin hose on request



Oil and Petroleum

- CNG dispensing application