

3TMH



PART	HOSE SIZE INFO												
#	DN	Hose I.D.		Hose O.D. max.		Operating Pressure		Min. Burst Pressure		Bend Radius		Weight	
		mm	in	mm	in	bar	psi	bar	psi	mm	in	kg/m	lbs/ft
3TMH-06	10	9.5	0.37	17.00	0.66	235	3,408	940	13,664	70	2.76	0.380	0.25
3TMH-08	12	12.7	0.50	20.60	0.81	245	3,553	980	14,200	80	3.14	0.495	0.32
3TMH-10	16	15.9	0.63	25.00	0.98	280	4,061	1,120	16,200	90	3.54	0.790	0.53

Operating Temperature

-40°C to 100°C
(-40°F to +212°F)

Type of fittings



Winner 2 piece
(EMEA only)



Danfoss 1A/Z

Option

Electrical cable
(with min. 3 lines)



Inner tube

Synthetic rubber

Reinforcement

Single or double wire


Cover

Polyurethane

Typical platforms

- Material handling
 - Telehandler
 - Forklifts
 - Telescopic booms
- Agriculture
- Horticulture
- Forestry delimbed
- General construction
- Utility vehicles and pickers

How to order/ part # structure



Packaging:


Continues length: single line
76.2 m, multiline up to 60 m
Random length: 1 or 2 pieces

3TMH Thermoplastic hose



PART		HOSE SIZE INFO		
#	Number of hoses	Hose I.D.		Length
		mm	in	meters
3TMH-06-2-250BX	2	19.0	0.74	76
3TMH-08-2-250BX	2	25.4	1.00	76
3TMH-10-2-250BX	2	31.8	1.25	76

How to order/ part # structure



Packaging:

Continues length: single line
76.2 m, multiline up to 60 m
with up to 3 random lengths,
cover 76 m or 60 m


3TB0 Constant pressure hose



PART			HOSE SIZE INFO		
#	Hose size	Number of hoses	Hose I.D.		Length
			mm	in	meters
3TB0-06-2-250BX	3TB0-06	2	9.7	0.37	75
3TB0-08-2-250BX	3TB0-08	2	13.0	0.50	75
3TB0-10-2-250BX	3TB0-10	2	16.2	0.63	75

* Contact Danfoss customer service for twin-line, tri-line,
and multi-line configuration options.

How to order/ part # structure



BC: continuous length in box
(76 m)

BX: minimum 6.5 m lengths,
with up to 3 random lengths,
cover 76 m

Options on demand

RL: random length reel

R: continuous length on reel

37B0 Medium pressure hose



PART			HOSE SIZE INFO		
#	Hose size	Number of hoses	Hose I.D.		Length
			mm	in	meters
37B0-03-2-250BX	37B0-03	2	4.8	0.19	75
37B0-04-2-250BX	37B0-04	2	6.4	0.25	75
37B0-05-2-250BX	37B0-05	2	7.9	0.31	75
37B0-06-2-250BX	37B0-06	2	9.5	0.37	75

* Contact Danfoss customer service for twin-line, tri-line,
and multi-line configuration options.