

3VE0



Hose construction:	Inner tube:	Reinforcement:	Cover:
	Nylon-lined	Spiral, high-tensile aramid fiber	Polyurethane

Operating temperature:	For water-based fluids: -40 °C to +66 °C (-40 °F to +150 °F)
-------------------------------	--

Hose color(s):	Orange perforated
-----------------------	-------------------

Approved Fitting:	90V/9AV/9CV
--------------------------	-------------



Part #	Size Dimensions						Pressure				Bend		Weight		Length	
	Hose Size	Hose I.D.		Hose O.D.			Max Operating Pressure		Burst Pressure		Min. Bend Radius		Weight		Length	
		DN	mm	in	mm	in	bar	psi	bar	psi	mm	in	Kg/m	lbs./ft	m	ft
3VE0-03	-03	5	4,8	0.19	13,2	0.52	689	10,000	2,758	40,000	38,0	1.50	0,11	0.08	76,2	250
3VE0-04	-04	6	6,4	0.25	15,1	0.60	689	10,000	2,758	40,000	64,0	2.50	0,16	0.11	76,2	250
3VE0-06	-06	10	9,5	0.38	19,8	0.78	551	8,000	2,206	32,000	76,0	3.00	0,23	0.16	76,2	250



General Hydraulic



Oil and Petroleum

- Used in sub sea & hydraulic application



Rescue Equipment



Forestry