


LPG

H900

Raven



Application

- For transfer and delivery of propane and butane
- Transfer of natural gas in open, well ventilated areas
(1 psiG max. working pressure)

Markets

- Alternative energy
- Propane transfer
- In-plant tank transfer
- Agriculture
- Construction
- General industrial

Construction

Tube Synthetic rubber

Reinforcement

Textile braid

Cover Pin-pricked synthetic rubber

Color Black

Operating temperature

-40°C to +82°C

(-40°F to +180°F)

Hose is capable of this rating. LP-Gas should never be elevated above 100°F.

Certifications

UL 21 rated
CAN/CGA 8.1 rated
(CSA 8.1-2015 on -20 & -24)

Number	Hose I.D.		Hose O.D.		Operating Pressure		Min. Burst Pressure		Weight		Length	
	mm	in	mm	in	bar	psi	bar	psi	kg/m	lbs/ft	mtr	ft
H90004-500R	6.4	0.25	14.9	0.59	24.0	350	122	1750	0.18	0.12	152.4	500
H90006-500R	9.5	0.38	18.4	0.72	24.0	350	122	1750	0.25	0.17	152.4	500
H90008-500R	12.7	0.50	23.3	0.92	24.0	350	122	1750	0.36	0.24	152.4	500
H90012-500R	19.0	0.75	31.2	1.23	24.0	350	122	1750	0.61	0.41	152.4	500
H90016-300R	25.4	1.00	38.1	1.50	24.0	350	122	1750	0.77	0.52	91.4	300
H90020-250RC	31.8	1.25	46.0	1.81	24.0	350	122	1750	1.09	0.73	76.2	250
H90024-250RC	38.1	1.50	52.1	2.05	24.0	350	122	1750	1.25	0.84	76.2	250

Coupling info:

Visit PowerSource crimp specs at danfoss.com/crimp for crimp specifications